



Changing The Can-Am Spyder RT Windshield

Step 1:

Before shutting down engine, raise windshield to highest point.

Step 2:

Remove T-25 Torx bolts from back side of windshield bracket. These are the fasteners that hold the windshield trim pieces on. Place bolts on seat with T-25 Torx tool.

Remove trim pieces by slightly pulling top of trim out from windshield and moving trim piece downward. This will release the trim piece from the windshield. Lay on seat, left and right side noted.

TIP: Place a playing card (or something similar) between the bottom point of the trim piece and the windshield. This will prevent the tip of the trim piece from gouging the windshield when the trim piece is removed.



Step 3:

Remove T-30 Torx mounting bolts (a second set of hands will be very useful) and remove windshield.





Changing The Can-Am Spyder RT Windshield

Step 4:

Lay windshield on large flat surface. You will see metal spacers inside the rubber mounting grommets. Remove these by pushing out of grommet with a round object (a #3 Phillips screwdriver is perfect for the job). Carefully remove the rubber mounting grommets from the shield by slowly working them out of the holes in the shield.



Step 5:

Lay new shield on large flat surface. Slowly work rubber grommets into mounting holes in new windshield. Be patient, these can be challenging at times. Once the rubber grommet is in place, push the metal spacer into the rubber grommet. Once you have completed all four, you are ready for your helper again.

INSTALLING NEW SHIELD

IF YOU HAVE HANDLED THE SHIELD AND HAVE FINGERPRINTS ON IT, BE SURE TO CLEAN THE AREA THAT WILL BE BEHIND THE MOUNTING BRACKET.

Step 6:

Hold the new shield up to the mounting bracket, moving slowly in order that the new shield (the glass itself) does not contact the metal bracket. Align the mounting holes and install the mounting bolts using care not to cross thread the bolts. Tighten snugly but do not overtighten.





Changing The Can-Am Spyder RT Windshield

Step 7:

Replace the trim pieces by placing L-shaped (don't forget the playing card) tab into bottom square hole in shield. Use gentle pressure to push in toward windshield and UP so tab locks onto shield. Square boss at top of trim piece should fall into place in square top hole. Install T-25 bolts to fasten trim piece.

TO FINISH:

Use your **favorite glass cleaner (or F4 Customs Windshield Cleaner)** and **paper towels** to clean your new shield. Now, you can "See Your Future Clearly!"

Thank you for your F4 Customs windshield purchase. If you have any difficulties regarding the replacement process, please feel free to contact us.



Questions? Comments?

sales@f4customs.com
www.f4customs.com
(330) 968-4644

***F4 Customs is not responsible for any injury or harm to either the individual or product resulting from the installation process.